

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 16 and 21

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3358-59)

Set a post 3½ ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on N. face, from which
A Fir 8" dia., bears S.29°E., 69 lks. dist. mkd. ¼ S BT
A Fir 20" dia., bears N.26°W., 7 lks. dist. mkd. ¼ S BT

BLM resurvey by C. Albert White;, Cadastral Surveyor and Donald R. Beck, Surveying Technician - under Group #427, Surveyed July/Aug. 1962 - (DCSO records Vol. 32 Page(s) 13329-30)

The ¼ sec. cor., determined at record bearing and distance from the original bearing trees:

A Fir 36" dia., bears N.26°W., 7 lks. dist., mkd. with a healed blaze.

A downed Fir 20" dia., bears S.29°E., 69 lks. dist., mkd. with a healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼ S 16
S 21
T 24 S R 8 W
1962

from which new bearing trees

A Fir 15" dia., bears N.10½°E., 46 lks. dist. mkd. ¼ S16 BT.

A Fir 9" dia., bears S.83°W., 62 lks. dist., mkd. ¼ S21 BT.