

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 9 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3361)

-----  
Set a post 3½ ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on N. face, from which  
A Fir 30" dia., bears S.30°W., 50 lks. dist. mkd. ¼ S BT  
A Fir 24" dia., bears N.35°W., 75 lks. dist. mkd. ¼ S BT

Survey by Nick Juliano - For: Weyerhaeuser Co. - Sept. 1969  
M 38-47

-----  
Found - Corner post gone.  
50" Fir N.34°W., 48.5 ft., scar visible.  
60" Fir S.38°W., 33.0 ft., scribe visible.  
Set 2" Iron pipe with brass cap.  
Referenced with "W" nails and plates:  
30" Maple S.21°E., 24.1 ft.  
50" Fir N.34°W., 48.1 ft., orig. BT.