

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCS0 records Vol. 8 Page(s) 3363)

Set a sandstone 14 x 10 x 4 ins. 9" in the ground, for ¼ sec. cor. marked ¼ S on W. face, from which
A Fir 16" dia., bears S.80½°E., 28 lks. dist. mkd. ¼ S BT
A Fir 20" dia., bears N.61¼°E., 32 lks. dist. mkd. ¼ S BT

Survey by Louis Prahr - For: Weyerhaeuser Co. - Aug. 1966 - C.S. File 55/11

Found - 17" Fir snag, old scar chopped out by me, no scribes, old "X" chopped into bark, N.81°E., 17.6 ft.
20" dead snag, chopped out by me, no scribes, found yellow metal tag and marks chopped in bark, N.61½°E., 21.1 ft.
Original stone with "¼".
Reference tree with BLM metal tag and marks chopped in bark on top ridge.
Corner is located on top of spur ridge which slopes eastward, at a point due East and 349 ft. horizontal from a reference tree located on top of main ridge.

Survey by Nick Juliano - For; Weyerhaeuser Co. - Sept. 1969 -M 38-47

Found - Corner stone mkd. "¼".
18" Fir snag, N.86°E., 18.5 ft.
24" Fir sng, N.62°E., 21.1 ft.
Set 1½" Iron pipe with brass cap, from which
Referenced with "W" nails and plates:
12" Fir, N.79°E., 63.4 ft.
16' Fir S.78°W., 16.1 ft.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Aug. 3, 1992 - C.S. File 64/31-3

Found - 1½" Iron pipe with a 1 3/4" screw on pipe plug brass cap, protrudes 7" above ground. Edge of stone visible long West edge of I.P., most of stone under a log. We did not disturb. Orig. stone.
20" now 22" dia., 10 ft. high rotted Fir snag with a previously opened blaze, no scribing visible, bears N.62°E., 22.0 ft. (Rec. N.62°E., 21.1 ft.)
(Cont. Next Page)

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

16" now 14" dia., 9 ft. high rotted Fir snag with a previously opened blaze, no scribing visible, bears N.81°E., 18.5 ft. (Rec. N.86°E., 18.5 ft.)
16" now 18" dia., 6 ft. high D.Fir stump with a healed notch near bottom of trunk, bears S.78°W., 17.0 ft. to center stump. (Rec. S.78°W., 16.1 ft. to nail)
NE. BT from 1969 is gone.
New BTs- 11" D.Fir, double blazed and scribed "¼ S4 CS BT", bears N.78½°E., 36.9 ft.
4" D.Fir, double blazed and scribed "X BT", tree is a pistol butt, bears N.49°E., 15.1 ft. to center of trunk.
7" pistol butt D.Fir, double blazed and scribed "¼ S9 CS BT" bears S.40°W., 28.0 ft. to center of root crown.

Fd. BC & 3 BTs + 3 BT stumps, 5/2008, by Ron Rice M156-12

Stephan Stys - Crew: Brandon Campbell & John Rondeau - 11/27/2022 - C.S. File 65/111-34

Found - A 1½" iron pipe w/1¾" brass cap w/ no markings set per map file M38-47.
An 11" D.Fir w/ healed face and tag bears N.49°E., 15.1' (Per CS 64/31-3).
A 22" rotten fir stump w/tag bears N.62°E., 22.0' (N.61°15'E 21.1' Per DCSO rec VOL 8 PG: 3363)
A 16" D.Fir w/healed face and tag bears N.78°30'E., 36.9' (Per CS 64/31-3).
A 14" rotten fir stump w/tag bears N.81°E., 18.5' (S.80°30'E., 18.5' Per DCSO rec VOL 8 PG: 3363).
A 17" D.Fir w/healed face and tag bears S.40°W., 28.0' (Per CS 64/31-3).
An 18" rotten fir stump w/tag bears S.78°W., 17.0' (S.78°W 16.1' Per CS 55/120-1C).
A galvanized post bears S.87°E., 0.7' (unknown record).
No new accessories.
Note - Lat. and long. per GARMIN ETREX HANDHELD GPS and does not produce survey grade coordinates.
N: 43°30'16.2" W: 123°39'16.6"
Compass declination: 18° East