

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 4

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GL0 Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCS0 records Vol. 6 Page(s) 2540)

Set a sandstone 18x12x6 ins., 12" in the ground for ¼ sec. cor. marked ¼ S on N. face, from which

- A Fir 10" dia., bears N.87°W., 46 lks. dist. mkd. ¼ S BT
- A Fir 14" dia., bears S.34°E., 17 lks. dist. mkd. ¼ S BT

Survey by Louis Prahar - For: Weyerhaeuser Co. - Aug. 1966 - C.S. File 55/11

Found - 1894 rock with ¼ on N. side.
1894 BT, now a windfall lying Eastward with face up, not chopped out, N.87°W., 30.4 ft.
1894 BT, S.34°E., 11.2 ft., now 14" dead snag, face open, scribes X chopped in bark.
6" Alder BT, S.38°22'E., 35.62 ft., dying, with Weyer. Alum. tag.

Set 5/8" Rod, 4.0 ft. tall, adjacent to rock and marked;
4 ft, dead Fir S.89°35'E., 4.6 ft., old "X" chopped in bark, placed Weyer. metal tag.

Corner is located 92.86, slope (81.09 horiz.) North of top of spur ridge which slopes Eastward towards Radar Creek, approx. ¼ mile Eastward down spur ridge from BLM, blacktopped Buck Mt. Road

Tony Hostetter - For: Weyerhaeuser Co - 8/2007 - C.S.65/60-34

Found - No evidence of 5/8" rods set by Prahar
14" snag, OBT, scribing visible, GL0 rec. S.34°E., 11.2 ft.

Set - 5/8"x36" rebar w/plastic cap mkd: "HOSTETTER LS 1075" at GL0 bearing & dist. from the 14" snag described above, from which

- 48" Fir stump, Prahar BT, no marks, bears East 6.0 ft. to center.
- 12" Hemlock, scribed "S4 ¼ BT", bears S.16°E., 23.9 ft. to 6" spike.
- 14" Fir, scribed "S ¼ BT" bears S.80°W., 32.7 ft. to 6" spike.
- 12" Fir, unrecorded BT, WEYCO tag (reads: S.8°E., 14.5 ft.) N.8°W., 14.2 ft. to 6" spike (new)

Fd. IR & 5 BTs - 5/2008, by Ron Rice M156-12

continued next page

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 340700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Stephan Stys - Crew: Brandon Campbell & John Rondeau -
11/27/2022 - C.S. File 65/111-33

-
- Found - A 5/8" iron rod w/ yellow plastic cap marked
"HOSTETTER LS 1075" Set per CS 65/60-34.
A 48" rotten fir stump bears N.90°E., 6.0'
(S.89°35'E., 4.6' per CS 65/60-34).
An 18" D.Fir w/visible scribe in face and tag bears
S.16°E., 23.9' (per CS 65/60-34).
A 19" uprooted D.Fir w/ healed face and tag bears
S.80°W., 32.7' (per CS 65/60-34).
A 17" D.Fir w/ healed face and tag bears N.8°W.,
14.2' (per CS 65/60-34).
A galvanized post bears S.60°E., 1.0' (unknown
record).
- New - A 12" D.Fir, faced & scribed "N¼ S4 BT" with X-chop
and tag bears S.74°W., 17.2' to a spike at side
center.
- Note - Lat. and long. per GARMIN ETREX handheld GPS (and
does not produce survey grade coordinates. 0
N: 43°31'09.9" W: 123°39'17.3"
Compass declination: 18° East.