

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 33; T23S R8W only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2554)

Set a sandstone 18x10x3", 12" in the ground at a point about 500 ft. above last gulch for ¼ sec. cor. marked ¼ on North face from which
A fir, 24" dia., bears N.36°W., 38 lks., mkd: ¼ S BT.
A fir, 30" dia., bears S.12½°W., 32 lks., mkd: ¼ S BT.

Ronald L. Rice, Ward NW - For: Roseburg Resources Co. - 5/2008 - M 156-12

Set - 5/8"x30" rebar with 2½" alum cap at tagged bearing & dist. from unrecorded BLM tag on BT. Cap mkd:
SC
T23S R8W
¼ S 33
2008
54633LS

- FD BT - 38" D.Fir bears S.7°E. 22.2' - bark scribing visible
- New BTs- 21" D.Fir bears S.61°E., 41.7' - blazed, scribed "X BT" at base.
- 7" Hemlock bears S.78°E., 29.9' - blazed, scribed "X BT" at base.
- 5" D.Fir bears N.44°E., 3.6' - blazed, scribed "X" at breast height & "BT" at base.

Note - This corner reset from the one BT in evidence. This tree carried a 1974 BLM tag with a bearing & dist. significantly different than the GLO record for any of the orig. accessories. This tree was bark scribed in the manner described by the GLO being "¼ S BT" with no section given. I accepted this as an orig. BT & accepted the bearing & dist. on the 1974 tag to reset the ¼ corner. My belief is that 1974 was prior to any logging activity & the person may have also had the orig. stone. No stone could be located but this position closely matches GLO record for the dist. & bearing to the N ¼ corner to the west (rec. West 2.40 chs). The bearing on the tag also matches the direction of the bark scribed face.