

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 8 Page(s) 3295)

Set Fir post 40" long, 5" dia., 20" in the ground for the cor. to secs. 33 and 34, from which
A Fir 18" dia., bears N.32°E., 100 lks. dist.
A Fir 60" dia., bears S.89°E., 10 lks. dist.
A Fir 48" dia., bears S.65°W., 34 lks. dist.
A Fir 18" dia., bears N.60°W., 48 lks. dist.

Fd. and tied in GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3303)

GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, Contract #779, dated Feb. 7, 1908 - (DCSO rec. Vol. 8 Page(s) 3384 & Vol. 10 Pg. 3985)

Intersect the old cor. of secs. 3, 4, 33 and 34, which is a post, firmly set, marked and witnessed as described by the Surveyor General, and which I afterward change to refer to secs. 33 and 34 T24S R8W only; and cut out bearing trees to the South.

See C.S. 42/206-1 by A. Evans for 1956 renewal not typed.

BLM Resurvey by Harold D. Corbin, Cadastral Surveyor, under Group #'s 350 and 427, Surveyed June 1959 - (DCSO records Vol. 30 Page(s) 12608)

The cor. of secs. 33 and 34 only, determined at record bearing and distance from the remains of the original bearing trees:

- A stump hole, with roots and bark of a Fir tree, bears N.32°E., 100 lks. dist.
- A sawed Fir stump 59" dia., bears S.89°E., 10 lks. dist., with axe marks and small portion of healed blaze facing the corner point; this tree was mkd. by Byars in 1878 and destroyed by Wygant in 1911 when he made the corner common to secs. 33 and 34 only.
- A sawed Fir stump 61" dia., bears S.65°W., 34 lks. dist., with axe marks and partially opened and burned blaze; the marks on this tree were destroyed by Wygant in 1911.
- A sawed Fir stump 52" dia., bears N.60°W., 48 lks. dist., with small portion of healed blaze remaining.

(Cont. Next Page)

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 and 34 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,
with brass cap mkd:

T 24 S R 8 W
S 33 | S 34
T 25 S R 9 W
S 3
1959

from which

A Hemlock 6" dia., bears N.10½°E., 23 lks. dist. mkd. T24S
R8W S34 BT.

A Hemlock 8" dia., bears N.78½°W., 59 lks. dist. mkd. T24S
R8W S33 BT.

Fd. and used in BLM resurvey by C. Albert White;, Cadastral
Surveyor and Donald R. Beck, Surveying Technician - under
Group #427, Surveyed July/Aug. 1962 - (DCS0 records Vol. 32
Page(s) 13319)

Fd. ok by D. Edwards, 3/2005 - M147-35