

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3342)

Set a sandstone 14 x 8 x 4 ins., 9" in the ground for 1/4 sec. cor. mkd. 1/4 on W. face, from which
A Fir 24" dia., bears N.55°W., 20 lks. dist. mkd. 1/4 S BT.
A Maple 12" dia., bears N.85°E., 40 lks. dist. mkd. 1/4 S BT.

BLM resurvey by C. Albert White;, Cadastral Surveyor and Donald R. Beck, Surveying Technician - under Group #427, Surveyed July/Aug. 1962 - (DCSO records Vol. 32 Page(s) 13320-21)

The 1/4 sec. cor., monumented with an unmarked sandstone 12 x 8 x 4 ins., firmly set 8" in the ground, from which the remains of the original NW. bearing tree:

A rotted Fir snag, 28" dia., bears N.45°W., 18 lks. dist. mkd. with old pitched face. (Rec. N.55°W. 20 lks.)

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 15" in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:

1/4
S 28 S 27
T 24 S R 8 W
1962

from which new bearing trees:

A Hemlock 12" dia., bears S.42°E., 38 lks. dist. mkd. 1/4 S27 BT.

A Hemlock 14" dia., bears N.67°W., 72 lks. dist. mkd. 1/4 S28 BT.