

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias	Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3345)

Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 15, 16, 21 and 22 marked, T24S S15 on NE.; R8W S22 on SE.; S21 on SW.; and S16 on NW. faces, with 3 notches on S. and E. edges, from which from
A Fir 54" dia., bears N.40°E., 56 lks. dist. mkd. T24S R8W S15 BT.
A Fir 24" dia., bears S.77°E., 43 lks. dist. mkd. T24S R8W S22 BT.
A Fir 26" dia., bears S.42°W., 40 lks. dist. mkd. T24S R8W S21 BT.
A Fir 24" dia., bears N.66°W., 31 lks. dist. mkd. T24S R8W S16 BT.

BLM resurvey by C. Albert White;, Cadastral Surveyor and Donald R. Beck, Surveying Technician - under Group #427, Surveyed July/Aug. 1962 - (DCSO records Vol. 32 Page(s) 13322-23)

The Sec. cor., determined from the remaining original bearing trees:
A Fir 40" dia., bears S.81°E., 40 lks. dist., slope dist., 43 lks. mkd. with a healed blaze. (Rec. S.77°E., 43 lks.) Reblaze and mark "T24S R8W S22 BT"
A Fir 47" dia., bears S.40°W., 40 lks. dist., no visible marks. (Rec. brg. S.42°W.) Reblaze and mark "T24S R8W S21 BT"
A Fir 48" dia., bears N.66°W., 29 lks. dist., slope dist., 31 lks. mkd. with a healed blaze. (Rec. dist. 31 lks.) Reblaze and mark "T24S R8W S16 BT"
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 24 S R 8 W
S 16 S 15
S 21 S 22
1962
from which a new bearing tree:
A Fir 14" dia., bears N.33½°W., 74 lks. dist. mkd. T24S R8W S15 BT.