

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3347)

Set a post 3½ ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on W. face, from which

A Fir 7" dia., bears N.31 3/4°W., 45 lks. dist. mkd. ¼ S BT.

A Fir 14" dia., bears N.12½°E., 41 lks. dist. mkd. ¼ S BT

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew June 16, 1971 - C.S. File 54/55-21

Found - Orig. 7" now 16" Fir, N.31 3/4°W., 29.7 ft., alive. Recently chopped open by BLM and shows "4S" scribe, reverse "S" found on chip laying on ground. Tagged.

Orig. 14" now 28" Fir, N.12½°E., 27.1 ft., alive, good axe scar and tagged. Cruiser mark "R/" on west side, 4 ft. above ground.

Set 1" I.P. & Brass cap at cor. mkd: County Surveyors Office
T 24 S R 8 W
¼ S16 | S 15
1971

New BT - 22" D.Fir N.43°W., 21.8 ft. mkd. ¼ S16 CS BT.
Corner lies on moderate West slope approx. 200 ft. West of the end of P-line at Sta. 34+80.