

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3349)

Set a post 3½ ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on W. face, from which
A Fir 50" dia., bears S.70°W., 11 lks. dist. mkd. ¼ S BT
A Fir 10" dia., bears N.28°E., 35 lks. dist. mkd. ¼ S BT

Survey by Nick Juliano - For: Weyerhaeuser Co. - Sept. 1969
M 38-47

Found - GLO corner post is gone.
16" Fir, down, N.30°E., 23.1 ft., scribe visible.
60" Fir S.38°W., 7.3 ft., scribe visible.
Set 1½" Iron pipe with brass cap.
Referenced with "W" nails and plates:
8" Hemlock N.65°E., 27.5 ft.
60" Fir S.38°W., 7.3 ft.