

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3352)

Set a post 3½ ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on W. face, from which
A Hemlock 8" dia., bears S.43°E., 11 lks. dist. mkd. ¼ S BT.
A Cedar 6" dia., bears N.55°W., 6 lks. dist. mkd. ¼ S BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew July 22, 1968 - C.S. File 54/55-19

Found - Orig. 8" now 16" Hemlock, alive, S.43°E., 7.3 ft., opened by BLM, scribe visible.
Orig. 6" now 14" Cedar, alive, N.55°W., 4.0 ft., scribe visible on nearly healed blaze. Rescribe "¼ S4 CS BT"
Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 8 W
¼ S 4 | S 3
1968
New BT - 17" Hemlock S.88°E., 14.1 ft. mkd. ¼ S3 CS BT.
Corner lies on top of spur sloping southerly to Rader Creek Junction.

Ronald L. Rice, Ward NW - For: Roseburg Resources Co. - 5/2008 - M 156-12

Found - 2½" brass cap dated 1968
19" Hemlock bears S.43°E., 7.3' - scribing visible
15" W.Red Cedar bears N.55°W., 3.4' - scribing visible.
New BTs- 47" D.Fir bears N.38°E., 26.3' - blazed, scribed "¼ S3 BT"
24" Hemlock bears S.53°W., 23.4' - blazed scribed "¼ S4 BT"