

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3351)

-----  
Set a post 3½ ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on N. face, from which  
A Fir 30" dia., bears S.23°E., 50 lks. dist. mkd. ¼ S BT  
A Fir 40" dia., bears North, 27 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyor Office - James Byron and crew - July 1968 - C.S. File 54/55-20

-----  
Looked For, not found. Falls in large slide area above Rader Creek Road.

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - Feb. 1970 - M 39-15

-----  
Corner set by proportionate measurement.  
Set 5/8" Iron rod and aluminum cap.  
Scribed- 6" D.Fir S.58°E., 26.9 ft.  
44" D.Fir N.31½°W., 55.4 ft.