

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias	Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3327)

Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 26, 27, 34 and 35 marked ,T24S S26 on NE.; R8W S35 on SE.; S34 on SW.; and S27 on NW. fces, with 1 notch on South and 2 notches on East edges, from which
A Chinquapin 15" dia., bears N.19°E., 27 lks. dist. mkd. T24S R8W S26 BT.
A Fir 60" dia., bears S.12°E., 26 lks. dist. mkd. T24S R8W S35 BT.
A Fir 30" dia., bears S.28°W., 31 lks. dist. mkd. T24S R8W S34 BT.
A Fir 12" dia., bears N.81°W., 68 lks. dist. mkd. T24S R8W S27 BT.

BLM corner remonumentation by Harold D. Corbin, Cadastral Surveyor, under Group #'s 350 and 427, Surveyed June 1959 - (DCSO records Vol. 30 Page(s) 12613-14)

The sec. cor., determined at record bearing and distance from the remains of the original bearing trees:
A rotted Chinquapin stump bears N.19°E., 27 lks. dist.
a Fir snag 50" dia., bears S.12°E., 26 lks. dist. with healed blaze.
A Fir snag 45" dia., bears S.28°W., 31 lks. dist. with healed blaze.
A Fir 20" dia., bears N.81°W., 68 lks. dist. with healed blaze.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:
T 24 S R 8 W
S 27 S 26
S 34 S 35
1959

from which
A Hemlock 9" dia., bears N.34°E., 33 lks. dist. mkd. T24S R8W S26 BT.
A Hemlock 8" dia., bears S.76°E., 30 lks. dist. mkd. T24S R8W S35 BT.
A Hemlock 6" dia., bears S.13½°W., 104 lks. dist. mkd. T24S R8W S34 BT.
A Hemlock 8" dia., bears N.17°W., 43 lks. dist. mkd. T24S R8W S27 BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias	Description

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1241, Surveyed April/May 1986 - (DCSO records Vol. 47 Page(s) 18123-24)

The sec. cor., monumented with an iron post 2½" dia., firmly set, projecting 5" above ground with brass cap mkd.in 1959 from which the remains of the original bearing trees:

A Fir snag 45" dia., bears S12°E., 23 lks. dist., with axe marks on a burned blaze. (Rec. 50" dia. 26 lks.)

A Fir snag 47" dia., bears S.28°W., 31 lks. dist. with opened and decayed blaze.

A root hole bears N.81°W., 68 lks. dist., with a decayed Fir 20" dia., lying alongside with scribe marks W S visible on opened blaze.

and the remains of bearing trees mkd. by Corbin:

A Hemlock 15" dia., bears N.34°E, 33 lks. dist. with scribe marks R8W S26 visible on partially healed blaze.

A Hemlock 12" dia., bears S.76°E., 30 lks. dist., with healed blaze.

A Hemlock snag 12" dia., bears S.13½°W., 104 lks. dist. with healed blaze.

and two new bearing trees:

A Fir 7" dia., bears S.47°W., 20 lks. dist. mkd. T24S R8W S34 BT.

A Cedar 8" dia., bears N.38°W., 28 lks. dist. mkd. T24S R8W S27 BT.