

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCS0 recs Vol 8 Pg 3329)

-----  
Set a post 3½ ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on W. face, from which  
A Fir 70" dia., bears S.57°W., 52 lks. dist. mkd. ¼ S BT.  
A Fir 60" dia., bears N.60°E., 10 lks. dist. mkd. ¼ S BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Oct. 19, 1966 - C.S. File 49/84-24

-----  
Found - Orig. 70" now 72" Fir, S.57°W., 34.3 ft., open and find "BT" scribe and reverse. Alive and shows faint upper scar.  
Orig. NE. BT turned out and slid downhill approx. 60 ft. and partially burned.

Set Brass cap at cor. mkd: County Surveyors Office  
T 24 S R 8 W  
¼ S27 | S26  
1966

New BTs- 11" D.Fir N.50°W., 12.7 ft. mkd. ¼ S27 CS BT.  
6" W.Fir S.10°W., 14.8 ft. mkd. ¼ S27 CS BT.  
7" D.Fir N.1°E., 9.4 ft. mkd. ¼ S26 CS BT.

Corner lies on very steep, NE. slope.

Douglas Co. Surveyors Office - Stephen J. Flause - Garrett McGraw - Nov. 17, 2010 - C.S. File 67/31-14

-----  
Found - No monument fd.  
One 1893 OBT found: A fir 70" dia., now a rotted but mostly intact 5½ ft. tall 60" dia., fir stump with a fully healed upper blaze & a previously opened lower blaze (no scribing found) bears S.57°W., 34.3 ft. (as per record)

Other OBTs gone.

Three BTs from 1966 renewal fd:

An 11: D.fir now a 20" DBH 15 ft. tall D.Fir snag with a fully healed double blaze bears N.50°W., 12.7 ft. (as per record)

A 6" W.Fir now a dead 17" DBH W.Fir with a fully healed double blaze bears S.12½°W., 14.8 ft., (Rec. S.10°W., 14.8 ft.)

A 7" D.Fir now a 12" DBH D.Fir with a fully healed double blaze bears N.10°W., 9.4 ft. (rec. N.01°E., 9.4 ft.) This tree according to the 1966 renewal is scribed "S26" we don not open to change scribing. (new BT tags we place on tree now indicate correct Sec. 27) cont.


TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Set - Due to agreement of bearing & distance to fd. OBT with record & agreement of distances measured to all other found BTs with record, a new monument is set for the corner at position indicated by accessories found.

New monument is a 2<sup>3</sup>/<sub>8</sub>" dia., brass cap on a 1<sup>3</sup>/<sub>8</sub>" O.D. by 30" long iron pipe firmly set protruding 8" above the ground. BC marked:  
Douglas County Surveyor



2010

A 12" DBH madrone, double blazed and scribed "1/4 S26 CS BT" N.27°E., 27.2 ft.

Near the top of a 4 ft. wide by 4 ft. tall, shallow, sandstone outcrop is marked, a "+" which measures 6" by 6" & bears N.81<sup>1</sup>/<sub>2</sub>°E., 10.7 ft.

Note - Monument is near top of steep east facing slope at westerly edge old growth forest which abuts older reprod forest.  
Compass decl. 16°E.