

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCS0 records Vol. 8 Page(s) 3329-30)

Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 22, 23, 26 and 27 marked ,T24S S25 on NE.; R8W S26 on SE.; S27 on SW.; and S22 on NW. faces, with 2 notches on S. and E. edges, from which
A Fir 36" dia., bears N.55°E., 89 lks. dist. mkd. T24S R8W S25 BT.
A Fir 18" dia., bears S.20°E., 70 lks. dist. mkd. T24S R8W S26 BT.
A Fir 30" dia., bears S.31°W., 109 lks. dist. mkd. T24S R8W S27 BT.
A Fir 30" dia., bears N.5°W., 60 lks. dist. mkd. T24S R8W S22 BT.

BLM corner remonumentation by Harold D. Corbin, Cadastral Surveyor, under Group #'s 350 and 427, Surveyed June 1959 - (DCS0 records Vol. 30 Page(s) 12614)

The sec. cor., determined at record distance from the remains of the original bearing trees:
A Fir 63" dia., bears N.55°E., 89 lks. dist. with healed blaze.
A rotted Fir stump bears S.20°E., 70 lks. dist.
A Fir 60" dia., bears S.34½°W., 109 lks. dist. with a healed blaze. (Rec. brg. S.31°W.)
A rotted Fir stump bears N.5°W., 60 lks dist.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:
T 24 S R 8 W
S 22 | S 23
S 27 | S 26
1959

from which
A W.Fir 8" dia., bears N.32°E., 19 lks dist. mkd. T24S R8W S23 BT.
A W.Fir 7" dia., bears S.62½°E., 21 lks. dist. mkd. T24S R8W S26 BT.
A W.Fir 8" dia., bears S.32°W., 26 lks. dist. mkd. T24S R8W S27 BT.
A W.Fir 9" dia., bears N.34°W., 42 lks. dist. mkd. T24S R8W S22 BT.

(Cont. Next Page)

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Oct. 19, 1966 - C.S. File 49/84-21

Found - 1959 Cadastral brass cap, properly marked.
Orig. 63" now 64" Fir, N.55°E, 58.7 ft., shows good scar. Alive, do not open.
8" now 11" D.Fir (not W.Fir) N.32°E., 12.5 ft., alive with healed blaze. Do not open.
7" now 13" D.Fir (not W.Fir) S.62½°E., 13.9 ft., alive with healed blaze. Do not open.
8" now 9" D.Fir (not W.Fir) S.32°W., 17.2 ft., alive, scribe marks visible on nearly healed blaze.

All other BTs destroyed by very recent logging.
New BT - 9" D.Fir N.1°W., 18.9 ft. mkd. T24S R8W S22 CS BT.
Corner lies approx. 100 ft. W. of road junction, roads E-N and S.

Fd. OK, March 1971, DCSO - C.S. File 54/55-26

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2102, surveyed May 2005 - Jan. 2006 - (DCSO records Vol. 56 Page(s) 22311 & Plat T24-8 2011)

The cor. of secs. 22, 23, 26, & 27, monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground with brass cap (properly) mkd.

from which the remains of the orig. BTs
A decayed fir snag, 52" dia., bears N.56¼°E., 58.7 ft with a healed blaze. (Rec. N.55°E.)

A decayed fir stump, size indeterminate, bears S.20°E., 46.2 ft. with no marks visible.

A decayed fir stump, 61" dia., bears S.33°W., 73.3 ft., with a healed blaze (Rec. S.34½°W., 71.9 ft.)

and remains of BTs mkd. by Corbin

A fir, 24" dia., bears N.32°E., 12.5 ft. with a healed blaze.

A fir, 20" dia., bears S.62½°E., 13.8 ft. with a healed blaze.

A dead fir, 9" dia., bears S.32°W., 17.2 ft. with a healed blaze.

and BT mkd by DCSO in 1966

A fir, 22" dia., bears N.1½°W., 18.8 ft. with a healed blaze.

and new BT

A fir, 28" dia., bears S.53¼°W., 43.2 ft., mkd: T24S R8W S27 BT.