

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCS0 records Vol. 8 Page(s) 3331)

Set a post 3½ ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on W. face, from which
A Yew 20" dia., bears N.87°E., 79 lks. dist. mkd. ¼ S BT.
A Fir 10" dia., bears S.25°W., 12 lks. dist. mkd. ¼ S BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew April/May 1966 - C.S. File 49/84-17

Found - Orig. 10" now 22" Fir S.25°W., 7.9 ft., opened and shows "¼S" scribe.

No trace of other orig. BT.

Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 8 W
¼ S22 | S23
1966

New BTs- 8" Hemlock S.5°W., 45.3 ft. mkd. ¼ S22 CS BT.
10" Hemlock S.61½°E., 55.6 ft. mkd. ¼ S23 CS BT.

Corner lies on steep (40°) N. slope and 50 ft. E. of small draw, course NE.