

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3331-32)

Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 14, 15, 22 and 23, marked ,T24S S14 on NE.; R8W S23 on SE.; S22 on SW.; and S15 on NW. faces, with 3 notches of S. and 2 notches on e. edges, from which
A Fir 15" dia., bears N.4°E., 25 lks. dist. mkd. T24S R8W S14 BT.
A Fir 14" dia., bears S.40°E., 33 lks. dist. mkd. T24S R8W S23 BT.
A Fir 40" dia., bears S.42°W., 27 lks dist. mkd. T24S R8W S22 BT.
A Fir 30" dia., bears N.15°W., 35 lks. dist. mkd. T24S R8W S15 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew May 1963 - C.S. File 49/84-10

Found - 2" squared wooded stake.
38" dead Fir snag N.15°W., 23.1 ft.(to face) cut open and found good scribing "BT"
26" Fir stub, N.4°E., 16.5 ft., opened previously, face rotted away.
Fir, old, uproot, down, S.42°W., 17.8 ft. Burl wood visible, bark gone.
Stump hole, Fir roots and portion of stump remaining, S.40°E., 21.8 ft.

Set Brass cap at cor. mkd: County Surveyors Office

T 24 S R 8 W
S 15 | S 14
S 22 | S 23
1963

New BTs- 6" D.Fir N.69°E., 9.8 ft. mkd. T24S R8W S14 CS BT.
14" W.Fir S.18°E., 28.2 ft. mkd. T24S R8W S23 CS BT
11" W.Fir S.57°W., 24.6 ft. mkd. T24S R8W S22 CS BT
8" D.Fir N.45°W., 30.4 ft. mkd. T24S R8W S15 CS BT.

Corner lies on steep NE. slope, approx. 100 ft. E. of top of ridge.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 3/17/26 - C.S. File 67/62-23

Found - 2½" DCSO brass cap.
21" D. Fir N.67°E. 10.8 ft. (Rec. N.69°E. 9.8 ft.) fully healed single blaze.

Continued next page

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

28" W. Fir S.18°E. 28.2 ft. fully healed single blaze.
22" D. Fir N.45°W. 30.4 ft. fully healed single blaze.
Steel post 2 ft. West.
Add 3½" mag nail right side center to all BTs.
New - No suitable trees to the S.W.
A 5/8" x 30 " Iron Rod with DCSO plastic cap proj. 3"
bears S.67½°W. 7.4 ft.
Compass decl. 14¼°E.
TRIMBLE GEO XT LOCATION
43°.47499194 N. 123°.62427624 W.