

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCS0 records Vol. 8 Page(s) 3334)

Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 10, 11, 14 and 15 marked, T24S S11 on NE.; R8W S14 on SE.; S15 on SW.; and S10 on NE. faces, with 4 notches on S. and 2 notches on E. edges from which

- A Fir 18" dia., bears N.48°E., 28 lks. dist. mkd. T24S R8W S11 BT.
- A Fir 30" dia., bears S.60°E., 28 lks dist. mkd. T24S R8W S14 BT.
- A Fir 24" dia., bears S.64°W., 67 lks. dist. mkd. T24S R8W S15 BT.
- A Fir 7" dia., bears N.71°W., 49 lks. dist. mkd. T24S R8W S10 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; C. Putnam, crew - Sept. 1960 - C.S. File 49/84-8

- Found - Orig. 30" now 44" Fir S.60°E., 18.5 ft., shows good scars.
Orig. 18" now 30" Fir N.48°E., 18.5 ft., shows good scars.
Orig. NW. BT, now stump hole only.
Orig. 24" now 44" Fir S.64°W., 44.2 ft., standing but center burned.

Set Brass cap at cor. mkd: County Surveyors Office

T 24 S R 8 W
S 10 | S 11
S 15 | S 14
1960

- New BTs- 9" R.Fir bears S.36°W., 19.4 ft. scribed S15 T24S R8W CS BT.
6" R.Fir bears N.52°W., 9.0 ft. scribed S10 CS BT.