

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCS0 records Vol. 8 Page(s) 3336-37)

Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 2, 3, 10 and 11 marked, T24S S2 on NE.; R8W S11 on SE.; S10 on SW.; and S3 on NW. faces, with 5 notches on S. and 1 notch on E. edges, from which
A Fir 12" dia., bears N.19°E., 118 lks mkd T24S R8W S2 BT.
A Fir 14" dia., bears S.80°E., 152 lks mkd T24S R8W S11 BT
A Fir 12" dia., bears S.85°W., 64 lks mkd T24S R8W S10 BT.
A Fir 20" dia., bears N.75°W., 94 lks mkd T24S R8W S3 BT.

Douglas Co. Surveyors Office - James W. Byron; M. Stone; G. Layne - Nov. 26, 1965 - C.S. File 49/84-13

Found - All orig. BTs which check for bearing and distance.
SW. BT, now snag, previously opened, shows good scribing.
NW. BT, blown down.
SE. and NE. BTs shows good scars.

Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 8 W
S 2 | S 3
S 10 | S 11
1965

New BTs- 10" R.Fir bears N.88°E., 14.0 ft. scribed S3 T24S R8W CS BT.
15" Laurel bears N.54°W., 15.0 ft. scribed S2 T24S R8W CS BT.
7" R.Fir bears S.58°W., 14.2 ft. scribed S10 CS BT.
13" W.Fir bears S.44°E., 14.7 ft. scribed S11 T24S R8W CS BT.

Fd. OK, May 1969 by DCS0, V. Tracy - C.S. File 54/55-5

Ron Quimby - Crew: N. Fromdahl & J. Ogden - 6/2019 - C.S. File 65/102-56

Found - DCS0 brass cap (properly mkd)
36" fir stump N.19°E., 77.9 ft. good scar.
50" fir S.80°E., 100.3 ft. good scar.
24" R.Fir N.88°E., 14.0 ft. good scar.
15" Fir stump S.58°W., 14.2 ft. good scar.
20" W.Fir stump S.44°E., 14.7 ft. good scar
Note - Compass decl. 15½°E.