TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3292)

Set ¼ sec. post, from which
A Maple 12" dia., bears N.70°W., 30 lks. dist.
A Cedar 10" dia., bears S.40°E., 58 lks. dist.

Fd. and tied corner in GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3327-28)

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1241, Surveyed April/May 1986 - (DCSO records Vol. 47 Page(s) 18124-25)

The ¼ sec. cor., determined from the remaining original bearing tree:
A Cedar 35" dia., bears S.40°E., 58 lks. dist., no marks visible on an opened and decayed blaze and with an old metal tag embedded in overgrowth. The tag is mkd. GLO T24S R8W ¼ COR.
At the corner point
Set an stainless steel post, 28" long, 2 1/2" dia., 20" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd: T 24 S R 8 W
¼ S 26 / S 35
from which new bearing trees
A Hemlock 28" dia., bears N.53°E., 102 lks. dist. mkd. ¼ S26 BT.
A Cedar 40" dia., bears S.9°E., 35 lks. dist. mkd. ¼ S35 BT.

Ronald L. Rice, Ward NW - Dec. 10, 2008 - C.S. File 65/63-40

Found - 3¼" brass cap dated 1986
35" W.Red cedar bears S.40°E., 38.3' - opened face, no marks visible
40" W.Red cedar bears S.9°E., 23.1' - scribing visible.
36" W.Fir (rec Hemlock) bears N.53°E., 67.3' - healed face
New BT - 28" Myrtle bears N.45°W., 51.6' - blazed, scribed "¼ S26 BT"
Note - Corner has steel post adjacent to it. All BT's have red painted bands and yellow tags.
Compass decl. 17°E.