

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCS0 records Vol. 8 Page(s) 3333)

Set a post 3½ ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on N. face, from which
A Cedar 30" dia., bears S.60°W., 8 lks. dist. mkd. ¼ S BT.
A Cedar 18" dia., bears N.15°E., 33 lks. dist. mkd. ¼ S BT

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; C. Putnam, crew - Nov. 7, 1960 - C.S. File 49/84-7

Found - Orig. 36" now 48" Cedar bears S.60°W., 5.3 ft., previously opened, shows good scribing "1 /"
Orig. 18" now 20" Cedar snag, N.15°E., 21.8 ft., center burned out.

Set Brass cap at cor. mkd: County Surveyors Office

T 24 S R 8 W

¼ $\frac{S\ 14}{S\ 23}$
1960

New BTs- 15" Hemlock bears N.17°W., 10.5 ft. scribed ¼ S14 CS BT.
48" Cedar bears S.60°W., 5.3 ft. rescribed ¼ S23 CS BT.

DCS0, Fd. BC & both BTs in good condition 5/1963 C.S. 49/84-9