

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCS0 records Vol. 8 Page(s) 3335)

Set a post 3½ ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on N. face, from which
A Fir 18" dia., bears N.78°W., 13 lks. dist. mkd. ¼ S BT
A Fir 30" dia., bears S.65°W., 13 lks. dist. mkd. ¼ S BT

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew April/May 1966 - C.S. File 49/84-20

Found - Orig. 30" now 42" Fir S.65°W., 8.6 ft., alive, shows good scar, open and find bottom of "S" scribe and reverse.
Orig. 18" now 32" Fir N.78°W., 8.6 ft., shows good scar, do not open.

Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 8 W
¼ S 11
S 14
1966

New BTs- 8" W.Fir N.36½°W., 16.3 ft. mkd. ¼ S11 CS BT.
8" D.Fir S.19°E., 21.0 ft. mkd. ¼ S14 CS BT.
Corner lies in shallow draw on bench on top of ridge.