

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCS0 records Vol. 8 Page(s) 3337-38)

Set a post 3½ ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on N. face, from which
A Fir 60" dia., bears S.15°W., 19 lks. dist. mkd. ¼ S BT
A Fir 20" dia., bears N.4°W., 61 lks. dist. mkd. ¼ S BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Aug. 1965 - C.S. File 49/84-12

Found - Orig. 20" now 40" Fir N.4°W., 40.3 ft., open and shows "1" scribed reverse.
Orig. 60" Fir S.15°W., 12.5 ft., now shattered stump and has slid down the hill approx. 6.0 ft. No scribe found.

Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 8 W
¼ $\frac{S \ 2}{S \ 11}$
1965

New BT - 10" D.Fir S.18°E., 10.5 ft. mkd. ¼ S11 CS BT.
Orig. 40" D.Fir N.4°W., 40.3 ft. mkd. ¼ S2 CS BT.
Corner is on very steep W. slope.

Ron Quimby - Crew: N. Fromdahl & J. Ogden - 6/2019 - C.S. File 65/102-57

Found - DCS0 brass cap (properly mkd)
40" Fir stump N.4°W., 40.3 ft. good scar.
New - 14" D.Fir N.23°E., 15.8 ft scribed ¼ S2 BT.
7" D.Fir S.5°E., 14.9 ft. scribed ¼ S11 BT.
8" D.Fir S.20°W., 21.0 ft. scribed ¼ S11 BT.
4" D.Fir N.26°W., 12.6 ft. scribed X
Note - Compass decl. 15½°E.