TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3292)

Set ¼ sec. post, from which
An Alder 6" dia., bears N.80°W., 23 lks. dist.
An Alder 12" dia., bears N.30°E., 56 lks. dist.

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3315-16)

Made careful search but could find no trace of the ¼ sec. cor. I again made careful search but could find no trace of the old ¼ cor.
Set a basalt stone 24 x 12 x 4 ins., 18" in the ground for ¼ cor. marked ¼ on West face, from which
A Laurel 16" dia., bears N.21°E., 100 lks. dist. mkd. ¼ S BT.
A Fir 20" dia., bears N.7½°W., 60 lks. dist. mkd. ¼ S BT

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1241, Surveyed April/May 1986 - (DCSO records Vol. 47 Page(s) 18121)

The ¼ sec. cor., monumented with a sandstone 24 x 12 x 4 ins., firmly set 12" in the ground mkd. ?4 on the E. face. (Rec. basalt stone mkd. on W. face.)
from which the remains of bearing trees mkd. by Chandler
A Madrone 28" dia., bears N.21°E., 102 lks. dist., no visible marks. (Rec. Laurel, 100 lks.)
A root hole bears N.9°W., 55 lks. dist., with a down Fir 35" dia. lying alongside, with healed blaze. (Rec. N.7½°W., 60 lks.)
At the corner point
Set an stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 24 S R 8 W
¼
S 35 S 36
1986

from which new bearing trees
A Fir 16" dia., bears N.60°E., 18 lks. dist. mkd. ¼ S36 BT
A Fir 12" dia., bears S.35°W., 28 lks. dist. mkd. ¼ S35 BT
Deposit the sandstone alonside and a white "DEEP-1" magnetic marker at base of stainless steel post.