TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3291)

Set qr. sec. post, _____, from which
A hemlock, 10" dia., bears N.35°E., 6 lks.
A hemlock, 10" dia., bears N.64°W., 14 lks.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2102, surveyed May 2005 - Jan. 2006 - (DCSO records Vol. 56 Page(s) 22311 & Plat T24-8 2011)

Point for the ¼ sec. cor. of secs. 25 & 36, at proportionate distance; there is no remaining evidence of the orig. corner.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 23" in the ground with brass cap marked: T24S R8W

¼
S 26|S 25
2005

from which
A fir, 18" dia., bears N.5½°E., 30.4 ft., mkd: ¼ S25 BT.
A hemlock, 17" dia., bears S.57½°W., 17.4 ft mkd: ¼ S26 BT
Deposit a magnet in a white plastic case at the base of the stainless steel post.