

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3318)

-----  
Set a post 3½ ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S. on W. face, from which  
A Fir 16" dia., bears N.75½°E., 101 lks. dist. mkd. ¼ S BT  
A Fir 36" dia., bears S.78½°W., 21 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - May 1, 1958 - C.S. File 49/84-1

-----  
Found both orig. BTs, both alive and in good condition and both check for bearings and distances. I open the NE. BT and find good scribing "S". I do not open the SW. BT, shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office  
T 24 S R 8 W  
¼ S23 | S24  
1958

New BTs- I rescribe now 35" R.Fir, N.75½°E., 66.7 ft. "¼ S24 CS BT"  
12" R.Fir S.47½°W., 40.2 ft. scribed "¼ S23 CS BT"

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Feb. 8, 1988 - C.S. File 62/50-8

-----  
Found - 1958 DCSO brass cap, properly mkd., on a 1 3/8" O.D. Iron pipe protruding 8" above ground.  
16" now 35" dia., 16 ft. high rotted D.Fir snag, orig. BT, illegible scribing found in previously opened blaze, rescribe visible on an unhealed double blaze, bears N.75½°E. 66.7 ft. (agrees w/rec.)

36" now 42" dia., 5 ft. high D.Fir stump tipped out of ground to NE. with possible evidence of face, bears S.78½°W., 13.9 ft. to root hole, (agrees w/rec. Orig. BT)

12" now 12" dia. D.Fir, out of ground, down and rotted, scribing visible on a partially healed double blaze "¼ S23 CS BT". Rec. position falls on logging skid road, BT was pushed out of position and now bears N.56°W., 32.3 ft. root wad.

New BTs- 9" D.Fir double blazed and scribed "¼ S24 CS BT" bears S.31°E., 7.0 ft.  
11" W.Fir double blazed and scribed "¼ S23 CS BT" bears N.66°W., 32.2 ft. Cont. Next page

Alias	Description
Alias	Description
Alias	Description
Alias	Description

	<p>7" D.Fir double blazed and scribed "¼ S23 CS BT" bears S.56¼°W., 18.5 ft. Corner lies approx. 700 ft. West of a dirt road on top of an E-W ridge.</p>
	<p>Ronald Rice - Roseburg Resources Co. - 6/2003 - M142-47 -----</p> <p>Found - 2½" County Surveyors brass cap dated 1958 with the following accessories: 35"x16' D.Fir snag bears N.75½°E., 66.7' (open face) 12" D.Fir bears S.31°E., 7.0' (healed face) 16" W.Fir bears N.66°W., 32.2' (healed face) 10" D.Fir bears S.56¼°W., 18.5' (healed face)</p> <p>New BT - 12" D.Fir bears N.13°E., 32.8' blazed, scribed "¼ S24 BT"</p> <p>Note - Existing corners or corner established as a result of this survey have a galvanized steel post adjacent to the corner monument and accessories have red painted bands &amp; BT tags where appropriate.</p>
	<p>Douglas Co. Surveyors Office - Crew: Stephen Flause &amp; Jeff Lorsung- 3/29/2019 (Filed 11/18/2021) - C.S. File 67/50-21 -----</p> <p>Found - 1958 DCS0 2½" dia., brass cap, (properly) marked, on a 1" I.D. iron pipe, set plumb, projecting 9" above ground. A 30" dia., 6 ft. tall rotted and broken Fir snag with a previously opened blaze showing rescribed "2" and "4" on a rotted face. This snag bears N.75½°E., 66.7 ft. (as per rec.) OBT A mostly rotted away tipped out Fir, the roothole of which bears S.78½°W., 13.9 ft. (as per rec.) OBT 1958 SW BT not found. A fallen 14" dia., D.Fir with FHDB, the roothole of this tree bears S.31°E. 7.0 ft (as per rec) 1988 A fallen 14" dia., D.Fir with FHDB, the roothole bears S.56¼°W. 18.5 ft (as per rec) 1988 A 19" dia., G.fir (lowland W.Fir) with FHDB; bears N.66°W., 32.2 ft. (as per rec) 1988 A 13" dia., 6 ft. tall D.Fir stump with a FHSB; bears N.13°E., 32.8 ft. (as per rec) 2003</p> <p>New - A 4" long "MAG NAIL" set in top center of an 8" dia., 11" tall solid Fir stump bears S.72½°E., 13.5 ft. A 21" dia., G.Fir scribed "¼ S23" "CSBT" on a double blaze; bears S.40°W., 33.7 ft.</p>