

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3320)

Set a post 3½" ft. long, 3" sq., 24" in the ground for ¼ sec. cor., marked ¼ S on W. face, from which
A Fir 36" dia., bears S.28°E., 12 lks. dist. mkd. ¼ S BT
A Fir 18" dia., bears N.32½°W., 72 lks. dist. mkd. ¼ S BT

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; C. Putman, crew - Nov. 7, 1960 - C.S. File 49/84-6

Found - Orig. 36" now 40" Fir snag, S.28°E., 7.9 ft. I open and find good scribing "¼"
Orig. 18" now 30" Fir, N.32½°W., 47.5 ft., shows good scars.

Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 8 W
¼ S14 | S13
1960

New BTs- 8" R.Fir bears S.32°E., 29.0 ft. scribed ¼ S13 CSBT
11" R.Fir bears S.45°W., 45.7 ft. scribed ¼ S14 CSBT

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 3/18/2021 (Filed 11/18/2021) - C.S. File 67/50-17

Found - 1960 DCSO 2½" BC on a 1" I.D. IP projecting 17" above ground is plumb added 18"x 1ft tall stone mound, now 5" (properly mkd)

A 31" dia., 18 ft tall D.Fir snag with a previously opened blaze; bears S.28°E., 7.9 ft (per rec) OBT

A 17" dia., D.Fir with FHDB; bears S.32°E., 29.0 ft. (per rec) 1960 DCSO

A 23" dia., 6 ft. tall solid D.Fir stump with FHDB; bears N.48°W., 45.7' (rec S.45°W., 45.7) 1960 DCSO

New - 10" dia., D.Fir scribed "¼ S13 CS" "BT" on a double blaze; bears N.0¼°E., 60.4 ft.

17" Madrone, scribed "¼ S13 CS" "BT" on a double blaze; bears N.85¼°E., 38.3 ft.

Note - BC mon is 50 ft east from gravel forest access road.
BC mon is on N-S cutline with very old second growth to east and new clearcut to west.