

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3320-21)

-----  
Set a post 4 ft. long, 4" sq., 24" in ground for cor. to secs. 11, 12, 13 and 14, marked T24S S12 on NE.; R8W S13 on SE.; S14 on SW.; and S11 on NW. faces with 4 notches on S. and 1 notch on E. edges, from which  
A Fir 10" dia., bears N.25°E., 80 lks. dist. mkd. T24S R8W S12 BT.  
A Fir 22" dia., bears S.10°E., 76 lks. dist. mkd. T24S R8W S13 BT.  
A Fir 20" dia., bears S.89½°W., 60 lks. dist. mkd. T24S R8W S14 BT.  
A Fir 18" dia., bears N.31°W., 49 lks. dist. mkd. T24S R8W S11 BT.

BLM corner remonumentation by Harold D. Corbin, Cadastral Surveyor, under Group #'s 350 and 427, Surveyed June 1959 - (DCSO records Vol. 30 Page(s) 12611)

-----  
The sec. cor., determined at record bearing and distance from the remaining original bearing trees:  
A Fir 30" dia., bears N.25°E., 80 lks. dist., with a healed blaze.  
A Fir 40" dia., bears S.10°E., 76 lks. dist., with a healed blaze.  
A Fir 30" dia., bears N.31°W., 49 lks. dist., with a healed blaze.  
At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:  
T 24 S R 8 W  
S 11 S 12  
S 14 S 13  
1959  
from which  
A Madrone 10" dia., bears N.56½°E., 14 lks. dist. mkd. T24S R8W S12 BT.  
A W.Fir 11" dia., bears S.43°E., 79 lks. dist. mkd. T24S R8W S13 BT.  
A W.Fir 6" dia., bears S.33½°W., 42 lks. dist. mkd. T24S R8W S14 BT.  
A W.Fir 37" dia., bears N.55½°W., 52 lks. dist. mkd. T24S R8w S11 BT.

continued next page

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Mark Smalley - For: Roseburg Resources - 11/13/2001 - C.S.  
File 65/40-7

-----

Condition report only

Found - 1959 Cadastral IPBC

9" Fir N.63°W., 28.2 good - healed (This BT was  
tagged & scribed in 1996 by Roseburg Resources)

14" Madrone N.56½°E., 9.2 good - healed.

22" Fir S.43°E., 52.1 good - healed.

16" Fir S.33½°W., 27.7 good - healed