

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3323)

 Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 1, 2, 11 and 12 marked , T24S S1 on NE.; R8W S12 on SE.; S11 on SW.; and S2 on NW. faces, with 5 notches on S. and 1 notch on E. edges, from which
 A Hemlock 18" dia., bears N.42½°E., 25 lks. dist. mkd. T24S R8W S1 BT.
 A Fir 60" dia., bears S.57°E., 45 lks. dist. mkd. T24S R8W S12 BT.
 A Fir 58" dia., bears S.63°W., 17 lks. dist. mkd. T24S R8W S11 BT.
 A Hemlock 18" dia., bears N.33°W., 58 lks. dist. mkd. T24S R8W S2 BT.

BLM corner remonumentation by Harold D. Corbin, Cadastral Surveyor, under Group #'s 350 and 427, Surveyed June 1959 - (DCSO records Vol. 30 Page(s) 12612-13)

 The sec. cor. determined at record bearing and distance from the original bearing trees:
 A rotted Hemlock snag, bears N.42½°E., 25 lks. dist. with scribe marks 24S R8W S1 and other illegible scribe marks visible on partially opened blaze.
 A Fir 60" dia., S.57°E., 45 lks. dist. with healed blaze.
 A Fir 48" dia., S.63°W., 17 lks. dist. with healed blaze.
 A Hemlock 30" dia., bears N.22°W., 58 lks. dist. with scribe marks 24 R8W S2 visible on partially opened blaze.

At the corner point
 Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 24	S R 8 W
S 2	S 1
S 11	S 12
1959	

from which
 A Hemlock 6" dia., bears N.49 3/4°E., 46 lks. dist. mkd. T24S R8W S1 BT.
 A Hemlock 6" dia., bears S.68¼°E., 54 lks. dist. mkd. T24S R8W S12 BT.
 A Hemlock 6" dia., bears S.33¼°W., 46 lks. dist. mkd. T24S R8W S11 BT.
 A Hemlock 10" dia., bears N.27°W., 40 lks. dist. mkd. T24S R8W S2 BT.

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Mark Smalley, Roseburg Forest Products - Party Chief: William Olson - June 2009 - C.S. File 65/66-25

Found - 1959 BLM Brass cap
Rotten Hemlock snag N.42½°E., 16.5' Stump 1893
60" Fir S.57°E., 29.7' Stump 1893
58" Fir S.63°W., 11.2' Stump 1893
30" Hemlock N.22°W., 38.3' Stump 1893
11" Hemlock S.68¼°E., 33.8' (rec 35.6') Healed face 1959
18" Hemlock N.26¾°W., 26.7' Healed face BLM 2005
12" Hemlock S.25°W., 50.4' Partially healed face BLM 2005
7" D.Fir N.52¾°E., 23.5' Partially healed face BLM 2005
6" Hemlock N.49°E., 30.4' 1959 Gone
6" Hemlock S.33¼°W., 30.4' 1959 Gone
10" Hemlock N.27°W., 26.4' 1959 Gone
Note - Compass decl. 18°E.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2104, surveyed July 2005/Jan. 2006 (DCSO records Vol. 57 Page(s) 22409-10)

The cor. of secs. 1, 2, 11 & 12, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.
from which the remains of the orig. bearing trees
A roothole bears N.42½°E., 16.5 ft., with fallen hemlock trunk, 24" dia., lying alongside, no marks visible.
A sawed fir stump, 66" dia., bears S.57°E., 29.7 ft., with a healed blaze.
A sawed fir stump, 63" dia., bears S.63°W., 11.2 ft., with a healed blaze.
A sawed hemlock stump, size indeterminate, bears N.22°W., 38.3 ft., with no marks visible.
and remaining bearing trees mkd. by Corbin
A hemlock, 12" dia., bears S.68¼°E., 33.8 ft., with a healed blaze. (Record, 35.6 ft.)
A hemlock, 18" dia., bears N.27°W., 26.4 ft., with a healed blaze.
and new bearing trees
A fir, 7" dia. bears N.52¾°E., 23.5 ft mkd. T24S R8W S1 BT
A hemlock, 13" dia., bears S.25°W., 50.4 ft., mkd. T24S R8W S11 BT.

Fd ok 5/2019, R Quimby C.S. File 65/102-49