

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 36; & S. 1, T25-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3291)

Set ¼ sec. post, from which
A Fir 15" dia., bears S.10°W., 15 lks. dist.
A Fir 24" dia., bears N.5°W., 56 lks. dist.

GL0 survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 8 Page(s) 3294)

Set a Fir post 40" long, 5" dia., 18" in ground for the qr. sec. cor. on S. bdy. of sec. 36, from which
A Fir 10" dia., bears S.50°E., 30 lks. dist.
A Fir 12" dia., bears N.27°W., 80 lks. dist.

Fd. corner in good condition in GL0 Survey by - A. R. and S.C.Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 8 Page(s) 3301)

BLM Resurvey by James E. Jelly; Harvey E. Wofford; Wayne L. Rogers, Cadastral Surveyors, under Group #'s 926 and 958 - Surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16430)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 24 S R 8 W
1/4 $\frac{S\ 36}{S\ 1}$
T 25 S
1979

from which
A Fir 6" dia., bears N.74¼°W., 35 lks. dist. mkd. ¼ S36 BT
A Fir 4" dia., bears S.2°W., 17½ lks. dist. mkd. ¼ S1 BT.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 3/28/2019 (Filed 11/18/2021) - C.S. File 67/50-20

Found - A 2½" o.d. iron pipe, firmly set, projecting 5" above the ground with a 3 1/4" diam. brass cap (Properly) marked
No evidence remains from the orig., 1878 or 1881 surveys. Area has been logged and burned several times.

BTs by Jelley for BLM in 1979 -

continued next page

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 36; & S. 1, T25-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 9"x1.5' tall solid D.Fir stump bears S.2°W., 11.6 ft with a fully healed blaze. (placed a 4" mag nail in the top center at record bearing & dist)

A 17" dia. Grand Fir bears N.72°W., 23.1 ft with a fully healed blaze. (record N.74¼°W.)

New BT- A double trunk madrone with an 8" and a 22" dia. trunk bears N.6°E., 6.4 ft, the larger trunk is scribed "T24SR8W¼S36", "BT" (bearing is to the base of the larger scribed trunk)

A 9" dia. D.Fir bears S.75°W., 7.7 ft., scribed "T25SR8W¼S1", "CSBT".

Note - The corner falls on a North slope on the edge of a recent clearcut in a mixed fir and madrone forest, approximately 75 ft. North of the gravel access road.

All BTs have BT Tags attached. All new BTs have double blazed faces with bearing measured to the center of the trees at the root crown and distances measured to a 4" mag nail in the side and center of the root crown.

Compass declination: 14¾°E.

GEODETIC COORDINATES DATUM: NAD 83

LAT: 43°25'57.265738513"N LONG: 123°35'41.959618650" W