

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 CORNER TO SECTIONS 25 & 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, deputy Surveyor under contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3291)

-----  
Set 1/4 sec. post, \_\_\_\_\_, from which:  
A Fir, 12" dia., bears N.7°E., 52 lks. dist.  
A Fir, 20" dia., bears S.32°E., 24 lks. dist.

Mark Smalley, surveyed for Roseburg Forest Products, Jan. 1999 - M131-12

-----  
Set - 5/8" x 48" iron rod & aluminum cap marked "LS 2354 1999"  
Scribed -  
14" W.Fir, N.3°E., 34.0 ft. "1/4 S BT"  
12" Fir, N.69°E., 28.7 ft. "1/4 S BT"  
18" Fir, S.34°W., 16.5 ft. "1/4 S BT"  
25" W.Fir, N.44°W., 25.3 ft. "1/4 S BT"

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2102, surveyed May 2005 - Jan. 2006 - (DCSO records Vol. 56 Page(s) 22311 & Plat T24-8 2011)

-----  
The ¼ sec. cor. of secs. 25 & 36, reestablished by Smalley in 1999, and is accepted as the cor., monumented with an iron rod, 5/8" dia., firmly set, projecting 12" above ground, with alum. mkd:

ROSEBURG RESOURCES COMPANY

T24S R8W  
      S 25  
¼    S 36  
      1999  
      LS 2354

from which BTs mkd by Smalley  
A fir, 13" dia., bears N.60½°E., 28.4 ft. with fragmentary scribe marks visible on a partially healed blaze.  
A fir, 20" dia. bears S.26½°W. 16.6 ft with a healed blaze  
A fir, 26" dia., bears N.51¾°W., 25.1 ft. with scribe marks ¼ S visible on a partially healed blaze.  
A fir, 17" dia., bears N.½°W., 33.9 ft with a healed blaze