TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3293)

Set ¼ sec. post, from which
A Fir 60" dia., bears S.80°W., 40 lks. dist.
A Laurel 12" dia., bears N.10°W., 62 lks. dist.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Sept. 21, 1971 - C.S. File 54/55-30

Looked for, not found.
No OBTs found at this time that can be positively identified.

Ronald Rice - Roseburg Resources Co - 6/2003 - M142-47

Set - 2½" Alum. cap on 5/8"x30" rebar, marked: T24S R8W
¼ S 24
S 25
2003
54633LS

12" D.Fir bears S.54½°E. 20.4' blazed-scribed "¼ S25BT"
13" D.Fir bears S.87°E. 13.3' blazed-scribed "¼ S25 BT"
12" W.Fir bears N.9°W. 12.3' blazed-scribed "¼ S24 BT"
11" W.Fir bears N.80°E. 15.0' blazed-scribed "¼ S24 BT"

Note -Existing corners or corner established as a result of this survey have a galvanized steel post adjacent to the corner monument and accessories have red painted bands & BT tags where appropriate.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2102, surveyed May 2005 - Jan. 2006 - (DCSO records Vol. 56 Page(s) 22311 & Plat T24-8 2011)

The ¼ sec cor. of secs. 24 & 25, reestablished by Rice, in 2003, and is accepted as the cor., monumented with an iron rebar, 5/8" dia., firmly set, projecting 2" above ground, with alum. cap (properly) mkd.
from which BTs mkd by Rice
A fir, 14" dia., bears N.76½°E., 14.9 ft., with scribe marks ¼ S24 BT visible on an open blaze.
A fir, 14" dia., bears S.57½°E., 20.4 ft., with scribe marks S25 BT visible on an open blaze.
A fir, 15" dia., bears S.85°W., 13.3 ft. with scribe marks ¼ S25 BT visible on an open blaze.
A fir, 14" dia., bears N.12¾°W., 12.1 ft. with scribe marks ¼ S24 BT visible on an open blaze.