

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCS0 records Vol. 8 Page(s) 3319-20)

-----  
Set a post 3 ft. long, 3½" sq., 24" in the ground for ¼ sec. cor., marked ¼ S on N. face, from which  
A Fir 48" dia., bears S.11°W., 20 lks. dist. mkd. ¼ S BT  
A Fir 36" dia., bears N.75°W., 37 lks. dist. mkd. ¼ S BT

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew and BLM crew - Oct. 1966 - C.S. File 49/84-22

-----  
Found - Orig. 48" now 52" Fir S.16°W. 13.2 ft (Rec S.11°W.), alive, shows good scar. We do not open.  
Orig. 36" now 36" Fir snag, N.75°W., 24.4 ft., previously opened, and shows "¼S" scribe.

Set Brass cap at intersection of dist. and brg. of NW. BT, set in mound of stone, mkd: County Surveyors Office

T 24 S R 8 W  
¼ S 13  
S 24  
1966

New BTs- 15" Hemlock N.64½°W., 39.3 ft. mkd. ¼ S13 CS BT.  
11" D.Fir S.44°E., 51.6 ft. mkd. ¼ S24 CS BT.

Corner lies at the foot of steep slope, changing to bench land to NW.

Ronald Rice - Roseburg Resources - 6/2003 - M142-47

-----  
Found - 2½" County Surveyors brass cap dated 1966 with the following accessories:

48" burned fir stump bears S.16°W., 13.2'  
36" burned rotted fir stump bears N.75°W., 24.4'  
12" D.Fir snag bears S.44°E., 51.6' (healed face)

New - 11" D.Fir bears S.45°W., 4.8' blazed, scribed "¼ S24 BT"

11" D.Fir bears S.88½°W., 54.3' blazed, scribed "¼ S24 BT"

7" D.Fir bears N.75°W., 25.6' blazed, scribe "¼ S13 BT"

10" D.Fir bears N.20°W., 36.5' blazed, scribed "¼ S13 BT"

Note - Existing corners or corner established as a result of this survey have a galvanized steel post adjacent to the cor. monument & accessories have red painted bands & BT tags where appropriate.