TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3322)

Set a post 3½ ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on N. face, from which
A Fir 24" dia., bears N.26½°E., 172 lks. dist. mkd. ¼ S BT
A Fir 72" dia., bears South, 50 lks. dist. mkd. ¼ S BT.

BLM corner remonumentation by Harold D. Corbin, Cadastral Surveyor, under Group #'s 350 and 427, Surveyed June 1959 - (DCSO records Vol. 30 Page(s) 12611-12)

The ¼ sec. cor., determined at record bearing and distance from the only remaining original bearing tree:
A dead Fir 65" dia., bears South 50 lks. bark scribed ¼ S.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: T 24 S R 8 W

¼ S 12 / S 13

1959

from which
A Fir 13" dia., bears N.77½°E., 20 lks. mkd. ¼ S12 BT.
A Hemlock 19" dia., bears S.60½°W., 16 lks. mkd. ¼ S13 BT.

Mark Smalley, Roseburg Forest Products - Party Chief: William Olson - Ralph McManis - April 1996 (Filed 10/29/2010) - C.S. File 65/69-51

Found - BLM BC
18" D.Fir N.77½°E., 13.2', healed face - BLM 1959
72" D.Fir South 33.0', 20' tall snag - GLO 1893
24" Hemlock S.60½°W., 10.6', visible scribe-BLM 1959
New BTs- 22" D.Fir N.5°E., 5' - Scribed "¼ S BT"
20" D.Fir S.9°W., 23.6' - Scribed "¼ S BT"

Ronald L. Rice, Ward NW - Sept 2010 - C.S. File 65/69-55

Found - 3¼" BLM brass cap dated 1959
26" D.Fir bears N.77½°E., 13.2' - healed face
29" Hemlock bears S.60½°W., 10.6' - scribing visible
25" D.Fir bears S.9°W., 23.6' - healed face
24" D.Fir bears N.5°E., 5.0' - healed face
65" rotted D.Fir staub bears South 33.0' - rotted face
Note - Corner has steel post adjacent to it. All BTs have red painted bands & yellow tags.