

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 643700

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 36 only, T23-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2551-52)

Set a post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor., from which
A Fir 30" dia., bears N.81°E., 21 lks. dist. mkd. ¼ S BT
A Fir 40" dia., bears S.62½°E., 44 lks. dist. mkd. ¼ S BT

Survey by Les Roberts, LS #1039 - For: International paper Co. - March 30, 1982 - M 91-74

No evidence of original corner.
Set 1½" x 36" I.P. with brass cap at proportionate distance.
New BTs- 9" Fir bears N.49°W., 12.8 ft., scribed.
12" Fir bears N.12°E., 10.8 ft., scribed.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2104, surveyed July 2005/Jan. 2006 (DCSO records Vol. 57 Page(s) 22404)

The ¼ sec. cor. of sec. 36 on the N. bdy of the Tp., reestablished by Roberts, in 1982, and is accepted as the cor., monumented with an iron post, 1¾" dia., firmly set, projecting 5" above ground, with brass cap (properly) mkd. from which the remains of bearing trees mkd. by Roberts
A high-sawn fir stump, 14" dia., bears N.14°E., 10.8 ft., with scribe marks ¼ S36 visible on a partially healed blaze.
A fir, 10" dia., bears N.48¼°W., 12.7 ft., with a healed blaze.
and new bearing tree
A fir, 22" dia., bears S.55¾°W., 15.6 ft., mkd. X BT.