

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 36; & 31, T24-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3194)

Set ¼ sec. post, from which
 An Oak 12" dia., bears S.80°W., 21 lks. dist.
 An Oak 12" dia., bears N.10°E., 95 lks. dist.

Fd. and tied in GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3314-15)

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Resources Co. - May 12, 1987 - M 104-16

Set a 5/8" x 48" Iron rod and aluminum cap, from which
 12" Fir bears N.84°E., 5.6 ft.
 19" Fir bears S.84°W., 22.5 ft.

M.Smalley for Roseburg Forest Prod. Jan. 1999 - M131-12

Set 5/8" x 48" iron rod & aluminum cap marked "LS 2354 1999"
BT's- 18" Fir, N.84°E., 5.6 ft. - healed
 24" Fir, S.84°W., 23.2 ft. (rec. 22.5 ft.) - healed
Scribed-
 14" Fir, S.7°E., 13.8 ft. "1/4 S BT"
 13" Fir, N.40°W., 20.0 ft. "1/4 S BT"