

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 25; & 30, T24-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3195)

Set ¼ sec. post, from which

A Fir 20" dia., bears S.2°E., 120 lks. dist.

A Fir 20" dia., bears N.70°W., 27 lks. dist.

Douglas County Surveyors Office - V.R. Tracy; J.W. Byron; Fritz Ingram - C.S. File 54/55-30 - Sept. 21, 1971

Corner searched for, not found.

Found logged and also OBT to South, would probably fall in slide area.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2102, surveyed May 2005 - Jan. 2006 - (DCSO records Vol. 56 Page(s) 22311 & Plat T24-8 2011)

The ¼ sec. cor. of secs. 25 & 30, on the E. bdy. of the Tp., determined at record bearing & dist. from the remains of the orig. BTs.

A sawed fir stump, 48" dia., bears S.2°E., 79.2 ft with scribe marks BT visible on opened blaze.

A roothole bears N.70°W., 17.8 ft. with fallen fir trunk, 49" dia., lying alongside, fragmentary scribes marks visible on bark blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 23" in the ground, with brass cap marked:

T24S

R8W R7W

¼

S 25|S 30

2005

from which

A fir, 14" dia., bears S.87½°E., 18.0 ft., mkd: ¼ S30 BT.

A fir, 16" dia., bears S.33°W., 23.4 ft., mkd: ¼ S25 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.