

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 700341

PRIMARY CORNER DESCRIPTION West 1/4 Cor. for Sec. 19 only, T24-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Les Roberts - For: International Paper Co. - Nov. 20, 1981 - M 90-12

Set 1½" x 36" I.P. and brass cap, from which new BTs:
22" Fir bears S.84°E., 9.9 ft., scribed.
23" Fir bears S.2°W., 20.0 ft., scribed.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2104, surveyed July 2005/Jan. 2006 (DCSO records Vol. 57 Page(s) 22391)

The ¼ sec. cor. of sec. 19 only, T24S R7W on the E. bdy. of the Tp., established by Roberts, Oregon in 1981, and is accepted as the cor., monumented with an iron post, 1¾" dia., firmly set, projecting 2" above ground, with brass cap (properly) mkd.

from which bearing trees mkd. by Roberts

- A fir, 28" dia., bears S.86¾°E., 9.8 ft., with a healed blaze.
- A sawed fir stump, 29" dia., bears S.1¼°W., 19.6 ft., with a healed blaze.