

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 700402

PRIMARY CORNER DESCRIPTION C C for secs. 18 & 19 only, T24-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3262)

-----  
At point of intersection, I set a sandstone 18x12x6 ins., 14" in the ground for closing cor. to secs. 18 and 19, marked CC with 3 notches on N. and S. edges, from which  
A Fir 36" dia., bears N.56°E., 91 lks. dist. mkd. T24S R7W S18 BT.  
A Cedar 12" dia., bears S.56°E., 42 lks. dist. mkd. T24S R7W S19 BT.  
A Fir 40" dia., bears N.64°W., 152 lks. dist. mkd. T24S R7W CC S18 and 19 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - S.A. Bilow, crew - May 20, 1959 - C.S. File 49/41-22

-----  
Found - Orig. 40" now 60" R.Fir N.64°W., 100.3 ft. I do not open, shows good scars.  
Orig. 12" now 14" Cedar snag, shows good scribing "S", S.56°E., 27.7 ft.  
Orig. 36" now 40" Fir snag, shows good scribing "BT", N.56°E., 60.1 ft.

Set Brass cap at cor. mkd: County Surveyors Office  
S 13 | S 18 T 24 S  
R8W | S 19 R7W  
1959

I find sandstone at corner as recorded. Set brass cap alongside corner stone.  
New BTs- 12" R.Fir bears N.22°E., 37.0 ft. scribed CC S18 T24S R7W CS BT.  
13" R.Fir bears S.72°E., 28.5 ft. scribed CC S19 T24S R7W CS BT.  
6" R.Fir bears S.79°W., 21.8 ft. scribed CC S13 T24S R8W CS BT.

Fd. OK, Nov. 20, 1981 by Les Roberts - M 90-12

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2104, surveyed July 2005/Jan. 2006 (DCSO records Vol. 57 Page(s) 22392-3)

-----  
The closing cor. of secs. 18 & 19, T24S R7W on the E. bdy. of the Tp., remonumented by the Douglas County Surveyors Office in 1959, monumented with an iron post, 1¼" dia., firmly set, projecting 19" above ground, with brass cap (properly) mkd. from which the remains of the orig. bearing trees cont.

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 700402

PRIMARY CORNER DESCRIPTION C C for secs. 18 & 19 only, T24-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A decayed fir stump, size indeterminate, bears N.56°E., 51.1 ft., with no marks visible. (Record, 60.1 ft.)  
A fir, 62" dia., bears N.64°W., 96.4 ft., with a healed blaze. (Record, 100.3 ft.)  
and remains of BTs mkd. by the Douglas Co. Surveyors Office  
A fir, 18" dia., bears N.21½°E., 36.6 ft., with a healed blaze.  
A fir, 20" dia., bears S.72¼°E., 27.5 ft., with a healed blaze.  
A fir snag, 7" dia., bears S.76¾°W., 22.1 ft., with fragmentary scribe marks visible on a partially healed blaze.