

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Sec. 13, East only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3221 & 3231)

Set a post, 3½ ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on W face, from which
A fir, 18" dia., bears N.81°E., 21 ft., mkd: ¼ S BT.
A fir, 16" dia., bears N.55°W., 56 lks., mkd: ¼ S BT.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2104, surveyed July 2005/Jan. 2006 (DCSO records Vol. 57 Page(s) 22393-4)

Point for the ¼ sec. cor. of sec. 13 only, on the E. bdy. of the Tp., at proportionate distance. There is no remaining evidence of the orig. cor.
Set a stainless steel post, 28" long, 2½" dia., 23" in the ground, with brass cap mkd.

T 24 S
R8W | R7W
¼
S13
2005

from which
A fir, 11" dia., bears N.86¾°W., 13.1 ft., mkd. ¼ S13 BT.
A fir, 11" dia., bears N.19¾°W., 11.4 ft., mkd. X BT.
Deposit a magnet in a white plastic case at the base of the stainless steel post