

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3266)

-----  
At point of intersection, I set a post, 4 ft. long, 4" sq., 24" in the ground for closing cor. to secs. 6 and 7, marked CC T24S R7W on E.; S6 on N.; and S7 on S.; with 5 notches on S. and 1 notch on N. faces, from which  
A Fir 50" dia., bears N.73°E., 40 lks. dist. mkd. T24S R7W S7 BT.  
A Fir 40" dia., bears S.2°E., 35 lks. dist. mkd. T24S R7W S7 BT.  
A Fir 24" dia., bears S.64°W., 34 lks. dist. mkd. T24S R7W CC S6 and 7 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - Sept. 1960 - C.S. File 49/41-47

-----  
Found - Orig. 50" Fir now 55", previously opened, shows good scribing "24S".  
Orig. 40" now 48" Fir S.2°E., 23.1 ft.  
Orig. 24" now 48" Fir, S.64°W., 22.4 ft.  
Set Brass cap at cor. mkd: County Surveyors Office  
CC | S 6 T24S R7W  
| S 7  
1960  
New BTs- 12" R.Fir bears S.82°E., 34.2 ft. scribed S7 T24S R7W CS BT.  
6" R.Fir bears N.70°E., 28.4 ft. scribed S6 T24S R7W CS BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Oct. 1967 - C.S. File 54/55-10

-----  
Found - DCSO brass cap, firmly set.  
Orig. 55" Fir, snag, to NE., shows scribe marks.  
Orig. 24" now 48" Fir, S.64°W., 22.4 ft., alive, top of scar visible in logging road fill.  
Orig. SE. BT, turned out and slid downhill approx. 15 ft.  
12" now 14" D.Fir S.82°E., 34.2 ft., alive, top broken out, healed blaze.  
6" D.Fir, turned out, N.70°E., 28.4 ft. scribe visible.  
New BT - 7" W.Fir N.60°E., 22.4 ft. mkd. T24S R7W S6 CC CSBT  
This corner lies 50 ft. E. of old logging road, course NW. on steep easterly slope. (Cont. Next Page)

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 700606

PRIMARY CORNER DESCRIPTION C C for Secs. 6 & 7 only, T24-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Les Roberts - For: International Paper Co. - July 1979 - M 80-47

-----  
Set 1½" I. Pipe and brass cap at true intersection, from which  
16" Fir bears S.82°E., 32.8 ft.  
11" Fir bears N.70°E., 27.0 ft.  
Corner lies 1.17 ft. West of County Corner.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under special instructions and Group No. 2104, surveyed July 2005/Jan. 2006 (DCSO records Vol. 57 Page(s) 22399-22400)

-----  
The true point for the closing cor. of secs. 6 and 7, at the intersection with the section line, established by Roberts, in 1979, and is accepted as the cor., monumented with an iron post, 1¼" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd.

from which a bearing tree by Roberts  
A fir, 24" dia., bears S.81°E., 33.6 ft., with a healed blaze. (Note: This bearing tree was mkd. by the Douglas County Surveyors Office in 1960 as a new accessory to the orig. closing cor. of secs. 6 and 7.)

From this point, the orig. closing cor. of secs. 6 and 7, established by Whipple in 1893-94, remonumented by the Douglas County Surveyors Office in 1960, and perpetuated by the Douglas County Surveyors Office in 1967, bears N.89°41'53"W., 1.18 ft., monumented with an iron post, 1¼" dia., firmly set, projecting 17" above ground, with brass cap (properly) mkd.

from which the remains of the orig. bearing trees  
A sawed and decayed fir stump, 41" dia., bears N.73°E., 24.0 ft., with scribe marks 24S 7W S6 visible on an opened blaze. (Record, 26.4 ft.)

A roothole bears S.2°E., 23.1 ft., with uprooted fir stump, 49" dia., lying alongside, no marks visible.

A fir, 45" dia., bears S.60°W., 22.4 ft., with a healed blaze. (Record, S.64°W.)

and bearing tree mkd. by the Douglas County Surveyors Office in 1960

A fir, 24" dia., bears S.81°E., 34.8 ft., with a healed blaze.

and BT mkd. by the Douglas County Surveyors Office in 1967

A fir, 20" dia., bears N.59½°E., 22.7 ft., with a healed double blaze.