

TOWNSHIP 24 RANGE 09 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Cor. Secs. 30 & 31 (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 8 Page(s) 3392)

Set fir post, 40" long, 5" dia, 18" in ground for the cor. to secs. 30 & 31, on W bdy, from which
A fir, 16" dia., bears N.52°E., 36 lks.
A fir, 24" dia., bears S.48°E., 25 lks.
A fir, 24" dia., bears S.60°W., 7 lks.
A fir, 18" dia., bears N.78°W., 26 lks.

Tony Hostetter - For: Weyerhaeuser Co. - Sept. 2015 - C.S. File 65/89-59

FOUND - 1/2" Copper pipe, listed in Weyerhaeuser Co records as being set in 1964 based on the found original BT listed below. From which:
40" Fir stump, OBT, tag and "W" nail, bears; S.60°W., 4.6 ft to center.
36" Fir stump, WEYCO tag and "W" nail, bears; N.53°W., 46.7 ft to "W" nail.
Note - Weyerhaeuser bearings typically measured by staff compass.
NEW - 14" fir stump, BT tag, bears N.39°E., 9.4 ft to 6" spike, placed below tag.
14" fir stump, BT tag, bears S.49°E., 1.6 ft to 6" spike, placed below tag
16" fir stump, BT tag, bears N.54°W., 21.9 ft to 6" spike, placed below tag
14" hemlock stump, BT tag, bears N.20°W., 9.8 ft to 6" spike, placed below tag
Note - New BT bearings determined by hand compass. Decl 18°E