

PRIMARY CORNER DESCRIPTION C C Secs. 7 & 18

Alias	Description

GLO survey by Levi C. Walker, Deputy Surveyor, under special instructions, dated Aug. 23, 1905, under contract 763 - (DCSO Records Vol. 8 Page 3469-3470)

Intersect W bdy. to Tp., 5.19 chs N.0°56'W., of the established cor. of secs. 7, 12, 13, & 18, which is a post firmly set marked & witnessed as described in the notes of W.H Byers under Contract N. 292 (DCSO records Vol. 8 page 3393) furnished by the Surveyor General.
This close being out of limits both in measurement and alignment, I retrace my work and find it correct.
I then return to the cor. of secs. 7, 12, 13, & 18, and after destroying all marks on the old cor. and bearing trees referring to secs. 7 & 18, at the point of intersection. Set a fir post, 3 ft. long, 4" sq., 24" in the ground, for CC of secs. 7 & 18, marked
CC T24S R9W on E, S7 on N, and S18 on S face, with 4 grooves on S & 2 grooves on N face; from which
 A fir, 30" dia., bears N.53°E., 30 lks., mkd: T24S R9E S7 BT.
 A fir, 24" dia., bears S.26°E., 38 lks., mkd: T24S R9E S18 BT.

Tony Hostetter - For: WEYCO -April 2012 - C.S. File 65/77-18

Found - 1/2" aluminum pipe. From which:
 40" fir stump, WEYCO tag & "W" nail OBT bears N.53°E., 19.8 ft.
 36" fir stump, WEYCO tag & "W" nail, scribing visible, OBT bears S.26°E., 25.1 ft.
New BTs- 19" fir, WEYCO tag, bears N.28°E., 13.3 ft to spike in root collar.
 15" fir, WEYCO tag, bears S.30°W., 13.7 ft to spike in root collar.
 14" fir, WEYCO tag, bears N.78°W., 8.2 feet to spike in root collar.