

TOWNSHIP 24 RANGE 09 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Levi C. Walker, Deputy Surveyor, under special instructions, dated Aug. 23, 1905, under contract 763 - (DCSO Records Vol. 8 Page 3470)

Set a fir post, 3 ft. long, 4" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on N and 18 on S face; from which
A fir, 30" dia., bears S.65°E., 20 lks., mkd: ¼ S18 BT.
A fir, 16" dia., bears N.22°W., 34 lks., mkd: ¼ S7 BT.

Tony Hostetter - For: WEYCO -April 2012 - C.S. File 65/77-17

Found - 1/2" alum. pipe
40" Fir stump, WEYCO tag & "W" nail, OBT bears S.65°E. 13.2 ft
28" Fir stump, WEYCO tag & "W" nail, OBT bears N.22°W. 22.4 ft
16" Fir, WEYCO tag, bears S.5°E., 9.8 ft.
New BTs- 16" Fir, WEYCO tag, bears N.9°E., 28.1 ft to spike in root collar.
14" Fir, WEYCO tag, bears S.75°E., 13.2 ft to spike in root collar.
14" Fir, WEYCO tag, bears N.10°W., 8.9 ft to spike in root collar

(DCSO has no rec. of any monuments or BTs other than the orig. BTs)