

TOWNSHIP 24 RANGE 9 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey Wm. Byers, Dep. Surveyor, Aug. 7, 1878, contract #292 - (DCSO records Vol. 8 Page(s) 3455-56)

-----  
Set a vine maple post, 3 ft. long, 4" sq. 24" in the ground, for ¼ sec. cor. mkd ¼ S31 on W and 32 on E face, from which  
A fir, 40" dia., bears N.20°E., 41 lks., mkd: ¼ S32 BT.  
A fir, 20" dia., bears S.6°W., 37 lks., mkd: ¼ S31 BT.

Tony Hostetter - For: Weyerhaeuser Co. - Sept. 2015 - C.S. File 65/89-60

-----  
Found - 3/4" iron pipe, set by Weyerhaeuser 1964 from OBT which was N.22°E., 22.8 ft (GLO: N.20°E., 27.1 ft) & OBT which was S.06°W., 25.8 ft (GLO: S.06°W., 24.4 ft). Both of these BTS are gone. The Weyerhaeuser information is from condensed corner book record, the 1964 field notes are not available. From which:

- 40" fir stump, WEYCO BT, no evidence, bears; S.38°30'E., 73.7 ft to center.
- 38" Fir stump, WEYCO BT, no evidence, bears; S.20°30'W., 59.1 ft to center.

Note - Weyerhaeuser bearings typically measured with a staff compass.

- NEW BTS-
- 25" Fir scribed "S32 ¼ BT", BT tag, bears: N.17°E., 10.4 ft to 6" spike, placed below face.
  - 12" Fir, scribed "S32 ¼ BT", BT tag, bears: S.48°E., 5.60 ft to 6" spike, placed below face.
  - 16" Fir, scribed "S31 ¼ BT", BT tag, bears: N.47°W., 12.8 ft to 6" spike, placed below face

Note - New BT bearings determined by hand compass (declination 18°E)