

TOWNSHIP 24 RANGE 09 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey Wm. Byers, Dep. Surveyor, Aug. 7, 1878, contract #292 - (DCSO records Vol. 8 Page(s) 3459-60)

Set a hemlock post, 3 ft. long, 4" sq., 24" in the ground, for cor. of secs. 19, 20, 29, & 30, mkd: T24S S20 on NE; R9W S29 on SE; S30 on SW; and S19 on NW face, with 2 notches on S & 5 notches on E edge; from which
A hemlock, 24" dia., bears N.54°E., 47 lks., mkd: T24S R9E S20 BT.
A hemlock, 24" dia., bears S.58°E., 14 lks., mkd: T24S R9E S29 BT.
A fir, 12" dia., bears S.30°W., 23 lks., mkd: T24S R9E S30 BT.
A hemlock, 12" dia., bears N.64°W., 19 lks., mkd: T24S R9E S19 BT.

Tony Hostetter - For: Weyerhaeuser Co. - June 9, 2015 - C.S. File 65/89-49

Found - 1/2" copper pipe (no DCSO record)
22" fir stump, scribing visible, OBT, bears S.30°W., 15.2 ft. to center.
New BTs- 20" fir, BT tag, bears S.48°E., 28.2 ft. to 6" spike, placed below tag.
11" fir, BT tag, bears S.01°E., 12.3 ft. to 6" spike, placed below tag.
16" fir, BT tag, bears N.33°W., 26.7 ft. to 6" spike, placed below tag.
17" fir, BT tag, bears N.07°W., 24.4 ft. to 6" spike, placed below tag.