

TOWNSHIP 24 RANGE 09 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey Wm. Byers, Dep. Surveyor, Aug. 7, 1878, contract #292 - (DCSO records Vol. 8 Page(s) 3463-4)

Set a hemlock post, 3 ft. long, 4" sq., 24" in the ground, for cor. of secs. 17, 18, 19, & 20, mkd: T24S S17 on NE; R9W S20 on SE; S19 on SW; and S18 on NW face, with 3 notches on S & 5 notches on E edge; from which
A Hemlock, 12" dia., bears N.86°E., 29 lks., mkd: T24S R9E S17 BT.
A Fir, 18" dia., bears S.88°E., 38 lks., mkd: T24S R9E S20 BT.
A Fir, 24" dia., bears S.26°W., 46 lks., mkd: T24S R9E S19 BT.
A Fir, 30" dia., bears N.68°W., 49 lks., mkd: T24S R9E S18 BT.

Tony Hostetter - For: Weyerhaeuser Co. - Feb. 2020 - C.S. File 65/106-9

Found - 1" iron pipe (no record)
12" Hemlock stump, WEYCO tag, scribing found on remnant of stump. bears N.86°E., 19.6 ft to center (GLO record N.86°E., 19.1 ft)
24" Fir stump, no marks, possible OBT, bears S.23°W. 31.4 ft to center. (GLO record S.25°W., 30.4 ft)
30" Fir stump, WECO TAG, possible OBT, bears N.69°W. 32.6 f to center. (GLO record N.68°W., 32.3 ft)
New BTs- 15" Fir tall stump, BT tag, bears N.86°E., 62.9 ft to 6" spike, placed below tag.
20" Fir tall stump, BT tag, bears S.51°W., 24.2 ft to 6" spike, placed below tag.
18" Fir tall stump, BT tag, bears N.68°W., 34.7 ft to 6" spike, placed below tag.
15" Fir tall stump, BT tag, bears N.02°W., 41.4 ft to 6" spike, placed below tag.