

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 8, only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey Wm. Byers, Dep. Surveyor, Aug. 7, 1878, contract #292 - (DCSO records Vol. 8 Page(s) 3408)

Set maple post, 40" long, 5" in dia., 20" in ground, for the 1/4 Sec. corner between Secs. 5 & 8, from which a
 Fir, 36" dia., bears North, 39 lks.
 Fir, 36" dia., bears south, 8 lks.

GLO retracement by Levi C. Walker, Deputy Surveyor, under special instructions, dated Aug. 23, 1905, independent of but in connection with his contract # 763, dated June 20, 1905 - (DCSO records Vol. 8 Page(s) 3428)

The 1/4 sec. cor, witnessed as described by the Surveyor General (old post gone) 4 bears North 39 lks. The true bearing of this line is therefore N.89°26'W. In place of the old post, I set a maple post, 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor. mkd: 1/4 S5 on N. face; from which
 A fir, 30" dia., bears N.33°E., 39 lks. (old BT)
 A fir, 36" dia., bears S.5°E., 8 lks. (old BT)

Tony Hostetter - For: Weyerhaeuser Co. - Feb. 2005 - C.S. File 65/54-14

Found - 1/2" conduit, as described in Weyerhaeuser Co. records. (No rec. in DCSO 3/28/2005)
 30" Fir stump, OBT - WEYCO, bears N.33°E., 26.2 ft. to center. (GLO: N.33°E., 25.7 ft.)
 40" Fir stump, OBT, axe marks WEYCO tag, bears S.5°E., 7.0 ft. to center (GLO S.5°E., 5.3 ft.)
New BTs- 21" Fir, scribed "S8 1/4 BT" WEYCO tag, bears S.31°W., 14.2 ft. to spike placed in root collar below scribing.
 18" Fir, scribed "S5 1/4 BT" WEYCO tag, bears N.40°W., 6.2 ft. to spike placed in root collar below scribing.
 14" Fir, scribed "S5 1/4 BT" WEYCO tag, bears N.00°W., 18.3 ft., to spike placed in root collar below scribing.