

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20 & 21

| Alias | Description |
|-------|-------------|
| | |
| | |
| | |
| | |

GLO survey Wm. Byers, Dep. Surveyor, Aug. 7, 1878, contract #292 - (DCSO records Vol. 8 Page(s) 3450)

Set a hemlock post, 3 ft. long, 4" sq., 24" in the ground, for cor. of secs. 16, 17, 20, & 21, mkd T24S S16 on NE; R9W S21 on SE; S20 on SW; and S17 on NW face, with 3 notches on S and 4 notches on E edge; from which
A fir, 24" dia., bears N.56°E., 63 lks., mkd: T24S R9W S16 BT.
A fir, 24" dia., bears S.83°E., 37 lks., mkd: T24S R9W S21 BT.
A fir, 30" dia., bears S.40°W., 17 lks., mkd: T24S R9W S20 BT.
A fir, 30" dia., bears N.7°W., 13 lks., mkd: T24S R9W S17 BT.

Tony Hostetter - For: Weyerhaeuser Co. - Sept. 2015 - C.S. File 65/89-63

Found - 1/2" alum. pipe set by Weyerhaeuser 1957. WEYCO Corner records indicate that the original corner post and 4 obts were found from which:
30" Fir, OBT, now stump, 2 WEYCO tags, "W" nail, bears; N.56°E., 41.6 ft to center.
30" decayed fir stump, OBT, WEYCO tag, bears; S.86°E., 24.4 ft to center.
42" fir stump, face evident, OBT, WEYCO tag and "W" nail, bears; S.40°W., 11.2 ft to center.
38" fir stump, face evident, OBT, "W" nail, bears; N.07°W., 8.6 feet to center.
Note - Weyerhaeuser bearings typically measured by staff compass.
New BTs- 16" fir stump, BT tag, bears; N.56°E., 41.5 ft to 6" spike, placed below tag.
13" fir stump, BT tag, bears; S.68°E., 29.8 ft to 6" spike, placed below tag.
17" fir stump, BT tag, bears; S.03°E., 6.8 ft to 6" spike, placed below tag.
11" fir stump, BT tag, bears; N.65°W., 3.2 ft to 6" spike, placed below tag.
Note - New BT bearings determined by hand compass (declination 18°E)