

TOWNSHIP 24 RANGE 09 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION CC Cor. Secs. 4 & 5 (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey Wm. Byers, Dep. Surveyor, Aug. 7, 1878, contract #292 - (DCSO records Vol. 8 Page(s) 3407)

Set dogwood post, 4 ft. long, 5" dia., 20" in ground on mound from which a,

- Fir, 24" dia., bears N.53°E., 71 lks.
- Fir, 24" dia., bears S.55°E., 40 lks.
- Fir, 30" dia., bears S.50°W., 46 lks.
- Fir, 48" dia., bears N.70°W., 34 lks.

GLO retracement by Levi C. Walker, Deputy Surveyor, under special instructions, dated Aug. 23, 1905, independent of but in connection with his contract # 763, dated June 20, 1905 - (DCSO records Vol. 8 Page(s) 3454)

The cor. of secs. 4, 5, 8 & 9, which is a post firmly set, marked & witnessed as described by the Surveyor General. This close, being in excess of the prescribed limits, I retrace my line & finding no error therein, I return & destroy all marks on the old cor. & BTs referring to Secs. 8 & 9

Tony Hostetter - For: Weyerhaeuser Co. Co. - March 2010 - C.S. File 65/69-6

Found - 3/4" iron pipe (1956 Weyerhaeuser records indicate that 1 original GLO BT was found. A 3/4 iron pipe was set at that time.) from which
40" fir stump, Weyco tag & "W" nail, bears: N.53°E., 46.9 ft to center (GLO: 24" fir, N.53°E., 71 lks)
New BTs- 14" Fir, Weyco tag & spike, bears N.30°E, 11.4 ft to spike.
16" fir, Weyco tag & spike, bears N.65°E., 12.9 ft to spike.
14" fir, Weyco tag & spike, bears S.17°E., 5.6 ft to spike.